

Product data sheet Characteristics

41EPBDWCLMZ-VW

Connected Dimmer, Iconic, Zigbee default mode, ControlLink, 300 W, 240 V, Vivid white





Main	
Range compatibility	Wiser hub Clipsal Iconic cover plate Pro Series cover plate
Product brand	Clipsal

Connected dimmer

Iconic

Complementary

Device presentation	Mechanism
Device application	Light control
Dimmer type	Universal
Load type	Dimmable LED: 0150 W Compact fluorescent lamp: 0300 W Incandescent lamp: 0300 W at 240 V Halogen lamp: 0300 W at 240 V LV halogen lamps: 0300 W (electronic transformer)
[Ue] rated operational voltage	220240 V AC 50 Hz
Protection type	Overheating protection Short-circuit protection Overcurrent protection
Colour	Vivid white (VW)
Local signalling	LED
Control type	Push-button By mobile application Multi-way control via ControlLink
Number of ways	5 ways
Software name	Wiser by SE App
Maximum number of connected devices	3 (dimmer) 2 (ControlLink module)
Cable length	50 m for ControlLink module
Technology type	Zigbee default Bluetooth low energy
Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period
Wiring configuration	3-wire
Material	Plastic
Mounting support	Grid
Device mounting	Flush
Fixing mode	Clip-in
Fixing center	84 mm
Type of installation	Indoor installation
Embedding depth	70 mm
Depth	56 mm

Product or component

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Width	48 mm
Height	22 mm

Environment

IP degree of protection	IP20	
Relative humidity	590 % non-condensing	
Standards	AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio	

Packing Units

I acking Office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	91.0 g
Package 1 Height	4.2 cm
Package 1 Width	6.8 cm
Package 1 Length	9.0 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	2304
Package 2 Weight	200.5 kg
Package 2 Height	95.0 cm
Package 2 Width	114.0 cm
Package 2 Length	114.0 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Weight	4.7 kg
Package 3 Height	22.7 cm
Package 3 Width	26.4 cm
Package 3 Length	33.8 cm

Offer Sustainability

Office Oddital lability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Life Is On